

SPECIFICATIONS

OUTLINE DRAWING

Modulation Input


Input Impedance
Digital Input (SMB Male)

50 Ohms
Standard TTL Levels

RF Output

Center Frequency (Fc)
Output Power (SMA Female)
Rise/Fall Time
RF Contrast Ratio
Harmonic Distortion
Output Impedance
Output VSWR
Bandwidth
Power Supply Voltage (Vcc)

350 MHz \pm 0.1%
1.0 W
3 nsec typ.
35 dB min
-30 dBc
50 Ohms
1.5 : 1 Max
230 MHz
+26 to +28 V @ 600 mA



Notes:

1. Output power factory set to 1.0 W at a 2.4 V, 30 mA input. Power stability less than 5% over the heat sink's ambient temperature range of 0-40° C, after 5 minute warm-up.
2. When calculating the contrast ratio, it is understood that only the power of the 350 MHz fundamental shall be used. The higher harmonics have no effect on the AO modulator's performance.

For Reference Only

THIS DOCUMENT IS THE PROPERTY OF CRYSTAL TECHNOLOGY, INC. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OTHER THAN BY EMPLOYEES OF CRYSTAL TECHNOLOGY AND ITS CONTRACTED REPRESENTATIVES AND DISTRIBUTERS. ANY EXCEPTION REQUIRES THE WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF CRYSTAL TECHNOLOGY.

TOLERANCES: .XX \pm .01 .XXX \pm .005	DR	T. Pham 7/15/1998	Crystal Technology, Inc. DESCRIPTION: AODR 1350AF-DIF0-1.0
MATERIAL:	CHK		
FINISH:	APP		
	APP	PART NUMBER: 97-02207-11	REV: 0
			1 of 1