

SPECIFICATIONS

OUTLINE DRAWING

Modulation Input


Input Impedance
Analog Input (SMB Male)

50 Ohms
0 to +1.0 VDC

RF Output

Center Frequency (Fc)
Output Power (SMA Female)
Rise/Fall Time
RF Contrast Ratio
Harmonic Distortion
Output Impedance
Output VSWR
Modulation Bandwidth
Power Supply Voltage (+Vcc)

200 MHz ± 0.1%
1.0 W
5 nsec Typ.
35 dB min
-30 dBc
50 Ohms
1.5 : 1 Max
75 MHz
+24 V @ 450 mA



Notes:

1. Output power factory set to 1 W at a 2.4 V, 30 mA input. Power stability less than 5% over the heat sink's ambient temperature range of 0-40° C, after 5 minute warm-up.
2. When calculating the contrast ratio, it is understood that only the power of the 200 MHz fundamental shall be used. The higher harmonics have no effect on the AO modulator's performance.

For Reference Only

THIS DOCUMENT IS THE PROPERTY OF CRYSTAL TECHNOLOGY, INC. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OTHER THAN BY EMPLOYEES OF CRYSTAL TECHNOLOGY AND ITS CONTRACTED REPRESENTATIVES AND DISTRIBUTERS. ANY EXCEPTION REQUIRES THE WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF CRYSTAL TECHNOLOGY.

TOLERANCES: .XX ± .01 .XXX ± .005	DR	A. Campi 12/3/1997	Crystal Technology, Inc. DESCRIPTION: AODR 1200AF-AIF0-1.0
MATERIAL:	CHK		
FINISH:	APP		
	APP		PART NUMBER: 97-02207-27
			REV: 0
			1 of 1